

# JS Cure Hard

## Clear Dustproofer and Hardener

**CONSTRUCTION IDEAS AT WORK**

LOT#

### PRODUCT DESCRIPTION

JS Cure Hard is a clear dustproofer and hardener for use on interior or exterior concrete surfaces. JS Cure Hard contains a unique and exclusive agent that penetrates the pores and capillaries of new or old concrete surfaces to chemically harden and dustproof. The penetrating action of JS Cure Hard changes free lime in the concrete to calcium silicate.

### GENERAL USES

JS Cure Hard is an excellent treatment for floors to receive asphalt, vinyl or rubber tile and adhesives for carpet. JS Cure Hard does not leave a residue that must be removed before floor coverings or adhesives can be applied to concrete.

JS Cure Hard is also an excellent treatment for base slabs to receive terrazzo or separate cement toppings.

### FEATURES

- One coat application.
- Safe to use.
- Sprayable—does not clog equipment.
- Resilient tiles, carpets, other floor treatments may be applied directly on JS Cure Hard-treated surfaces.

- VOC compliant.
- No deleterious effort upon the natural bonding characteristic of secondary toppings and coatings.
- Consult all manufacturers written instructions.

### STANDARDS

USDA accepted for use in federally inspected meat and poultry plants.

### INSTRUCTIONS FOR USE

Apply JS Cure Hard when concrete is dry to the touch, or when forms have been removed. Insure that form coatings other than oils have been used. Apply by spray or roller. **DO NOT ALLOW CURE HARD TO PUDDLE.** Brush out puddles as soon as possible.

### *Approximate coverage per square feet per gallon Curing, Hardening, and Dustproofing:*

|                       |                               |
|-----------------------|-------------------------------|
| Hard Troweled Finish  | 300-500 ft <sup>2</sup> /gal. |
| Broom or Float Finish | 200-400 ft <sup>2</sup> /gal. |
| Rough Finish          | 200-300 ft <sup>2</sup> /gal. |
| Aged Surface          | 200-300 ft <sup>2</sup> /gal. |
| Vertical Surface      | 200-300 ft <sup>2</sup> /gal. |

### LIMITATIONS/WARNING

- Refer to Material Safety Data Sheet before use.
- Designed for use on concrete and masonry only.
- Do not spray on glass, brick, aluminum, etc.
- If accidentally sprayed on other surfaces, wash with clean water before drying.
- Not recommended for use on colored floor surfaces.
- Do not use over colored concrete.
- Do not allow to freeze.
- Do not over apply.

### TECHNICAL SERVICES

Jobsite Supply Technical Service Department provides complete product and technical support.

### PACKAGING

- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

### KEEP PRODUCT OUT OF REACH OF CHILDREN



HIMS  
Hazard Ratings  
0 - Least  
1 - Slight  
2 - Moderate  
3 - High  
4 - Extreme



**DANGER**  
Keep away from heat, sparks & flames. Do not cut, puncture or weld on or near empty or full containers. Do not re-use container for any purpose, until commercial clean