

CONSTRUCTION IDEAS AT WORK

LOT#

PRODUCT DESCRIPTION

JS Super 2 is a premium, chemically reactive, citrus-scented petroleum based form release agent. JS Super 2 Form Release reacts with the alkali in the concrete to form a soap film that inhibits the bonding of fresh concrete to the formwork. Forms are ready for re-use almost instantly. JS Super 2 Form Release produces a smooth, void free, architectural concrete surface. VOC compliant.

GENERAL USES

JS Super 2 Form Release will aid in the release of the form from hardened concrete on the widest range of forming materials.

FEATURES

- Ensures easy stripping of forms.
- Produces smooth natural architectural surfaces – chemical action is not harmful to the concrete surface.
- Will not retard, etch, or soften concrete surfaces, even if over-applied.
- Run-down is reduced and reinforcing steel stays cleaner.
- May be used on concrete structures that will store portable water.
- Has a positive release that keeps forms clean – no cleaning between pours is necessary.
- Repeated use makes wood forms water-repellent and extends their useful life.
- Inhibits rust formation on steel forms.
- Easy to apply.

- No deleterious effect upon the natural bonding characteristics of secondary toppings or coatings, caulks, or sealants.
- Reduces bug holes and extends the life of most forming materials.

STANDARDS

This product meets the requirements of Corps of Engineers specifications CW 03101, section 2.1.2.

INSTRUCTIONS FOR USE

JS Super 2 Form Release should be applied in a thin uniform film with a sprayer, brush, or roller. No special application equipment is necessary, but a spray application is the most practical. Pounding or puddling is to be avoided.

Specific applications are as follows:

Aluminum, High Density Plywood, Plastic or Steel
2,000 sq. ft./U.S. gallon

Medium Density Plywood
1,500 sq. ft./U.S. gallon

BB Grade Plyform
1,200 sq. ft./U.S. gallon

Plywood & Other Dimensional Lumber
1,000 sq. ft./U.S. gallon

LIMITATIONS/WARNING

- Refer to Material Safety Data Sheet before use.
- Do not over apply.
- Do not use as a bondbreaker for tilt-up construction.
- Do not use on styrofoam or latex molds.
- Do not use on plaster molds unless coated with a suitable sealer.
- Colder temperatures will increase the viscosity of JS Super 2 Form Release.

Combustible... Contains petroleum distillates. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame.

TECHNICAL SERVICES

Jobsite Supply Technical Service Department provides complete product and technical support.

PACKAGING

- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

KEEP PRODUCT OUT OF REACH OF CHILDREN



HIMS
Hazard Ratings

- 0 - Least
- 1 - Slight
- 2 - Moderate
- 3 - High
- 4 - Extreme



DANGER
Keep away from heat, sparks & flames. Do not cut, puncture or weld on or near empty or full containers. Do not re-use container for any purpose, until commercial clean