

MATERIAL SAFETY DATA SHEET

Information Phone # 1-800 874 7415
Latest Revision Date: 4.29.2003
EMERGENCY PHONE #: 1-800 535-5053

Jobsite Supply
624 S. Missouri
Indianapolis, IN 46225

SECTION I PRODUCT IDENTIFICATION

CAS#	N/A
TRADE NAME OR CHEMICAL NAME	JS Form Release
CHEMICAL FAMILY	Modified Petroleum Oils
HMIS RATING	HEALTH = 1, FIRE = 2, REACTIVITY = 0. PERSONAL PROTECTION: (see section 7)

SECTION II HAZARDOUS INGREDIENTS

INGREDIENT	REFINED PETROLEUM OIL	Fuel Oil no. 2	Mineral Oil	Petroleum Oil
CAS#	64742-58-1	068476-30-2	64742-53-6	N/A
ACGIH TLV/TWA	N/A	N/A	N/A	N/A
ACGIH TLV/STEL	N/A	N/A	N/A	N/A
OSHA PEL/TWA	N/A	N/A	N/A	N/A
OSHA PEL/STEL	N/A	N/A	N/A	N/A
LD50, Oral	N/A	N/A	N/A	N/A
LD 50, Dermal	N/A	N/A	N/A	N/A
LD 50, Inhalation	N/A	N/A	N/A	N/A
PCT BY WT:	0-60	0-40	0-40	0-60

SECTION III PHYSICAL DATA

Physical State	N/A	Specific Gravity	0.9
Appearance	Redish Brown liquid	VOC	< 450 g/L
Odor	LOW ODOR	pH	N/A
Boiling Range	N/A	Freezing Point	N/A
Vapor Pressure	<0.5 ISOTENSISCOPE	Water Solubility	INSOLUBLE

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Lowest Closed Cup Flashpoint	Above 140°F
OSHA Flammability Classification	N/A
DOT Flammability Classification	Combustible
Lower Flammable Limit in Air	N/A
DOT Shipping Name	N/A
Flash Points	Above 140 °F
Mechanical Impact Explosion	N/A
Static Electricity Explosion	N/A
EXTINGUISHING MEDIA	DRY CHEMICAL OR CO2 IS PREFERRED

UNUSUAL FIRE AND EXPLOSION HAZARDS:
KEEP CONTAINER TIGHTLY CLOSED AND ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

SPECIAL FIRE FIGHTING PROCEDURES:
FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

DO NOT STORE ABOVE 100 °F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM HEAT, SPARKS AND FLAME.KEEP CONTAINERS CLOSED WHEN HOT IN USE AND UPRIGHT TO PREVENT LEAKAGE.

OTHER PRECAUTIONS:

DO NOT TAKE INTERNALLY. WASH HANDS AFTER USING AND BEFORE SMOKING OR EATING. ANY EMPTIED CONTAINERS MAY RETAIN HAZARDOUS RESIDUE AND EXPLOSIVEV APORS. KEEP AWAY FORM HEAT, SPARKS AND FLAMES. DON'T CUT OR WELD ON OR NEAR EMPTIED CONTAINERS. FOLLOW ALL HAZARDPRECAUTIONS GIVEN IN THIS SHEET UNTILL CONTAINER IS THOROUGHLY CLEANED OR DESTROYED.

SECTION X SARA TITLE III INFORMATION

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: N/A

NAME					
CAS#					
PC. WEIGHT					

SECTION XI TRANSPORTATION INFORMATION

D.O.T. SHIPPING NAME	Combustible liquid n.o.s.
D.O.T. HAZARD NAME	Combustible liquid
PACKING GROUP	III
U.N. NUMBER	NA 1993

DISCLAIMER AND LIMITATION OF LIABILITY

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of the Jobsite Supply Company's knowledge; however, The Jobsite Supply makes no warranty whatsoever, expressed or implied of MERCHANTABILITY or FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained form the use thereof. The Jobsite Supply assumes no responsibility for injury to recipient or to third persons or for any property and recipient assumes all such risk.